

Install auto-pilot.

Change primary fuel filters every 200 hrs.

" secondary " " " " 400 "

2700 no load RPM, 2450-2500 under load, 85% top RPM is cruising speed.

Install sail.

dependable life raft ^{12-13'} and small outboard motor.
Direct ^{exhaust under} water.

Install below water level viewing window.

Paint boat and varnish.

Teak floor

Bimini

4 plastic chairs

modify starboard side main cabin to full size bed and raise seats to full outside viewing level.

Remove port side seats and replace with 2 comfortable seats and provide wall table.

Two individual adjustable helm seats.

Fill in V berth in fore-cabin.

Install Sat-Nav.

Cellular phones ^{wind}

Install wind & speed indicator

Second anchor

Diesel generator.

Paint bottom of boat and clean cockpits, replace needed zinc plates

Install holding tanks

Clean bilge & paint bilge floor boards & above

Secure batteries

Connect proper wire for cabin heater. Insert gate valve.

Place solar panel & provide several ^{on} outlets.

Install shallow waterproof cabinet (Cabin wall) for drying ropes, etc.

Duplicate fiber packing rings

Tighten limber chain

Remove pan under motor and install section pans

Spring on stop lever.

Replace anchor chain from 3/8" to 1/2"

2 rear view mirrors

Odometer for speed & mileage

Shade tent over boom

Hand compass