SWIMMING POOL OPERATION

I. To Backwash

Shut off chlorinator
Shut off pump motor
Open 1 (drain)
Close 4 (from pool)
Close 6 (into pool)
Open 5 (into filter)
Open 3 (from main) Use 3 to control water washing filter;
Open slowly and close slowly.
Run until water is clear

II. To Filter

Close 5
Close 1
Open 6
Open 3
Start pump motor and open 4 slowly
To chlorinate, see VI

- III. To add Heat -- (Maintain pool temperature at 78°)
 Start filter circulation as in II
 Open 4 (steam)
- IV. To add Water -- [Maintain pool level at one brick below blue line for beginners, and at level of rail for competition)

 Stop pump close Now 4 valve

 Open 6

 Close 3

 Open 5
- V. To lower Water
 Open large valve in bottom of pit
- VI. To Chlorinate
 Start filter circulation as in II
 Open chlorinator gas tank valve
 Open water valve to 40 pounds pressure
 Be sure that lighted lamp is next to mixing chamber
 Be sure that water in middle tube is up to line
- VII. To shut off system

 Close chlorine tank valve

 Shut off chorinator water

 Close 4

 Shut off pump motor
- VIII. In Case of

 Electrical trouble, call K.U. 59, ask for Mr. Firner
 Plumbing trouble, call K.U. 70, ask for Mr. Eberhart
 Emergency, call K.U. 6, ask for Mr. Bayles